FleetZOOM®

: (877) 535-ZOOM
: Sales@FleetZOOM.com
: www.FleetZOOM.com

FZ100

Cellular Monitoring System

Overview:

The FZ100 is a compact cellular transceiver for monitoring industrial equipment that sends live data to the monitoring web site, providing real-time status and alarms. It features 3 digital inputs and 1 digital output. In addition to alarming on status changes, the system keeps track of on-time and cycles for the digital inputs; useful for monitoring pump, fan, or compressor run times and duty cycles. The unit monitors input power voltage and provides an optional battery backup which enables the system to alarm on main power voltage level or failure and continue operating without main power.

The easy to use web site updates continuously, displaying location and operating status for all of your monitored equipment. Alarms are immediately displayed on the web site and trigger messages sent to interested personnel in your organization via SMS text messages and emails. Every event is permanently logged in the web site allowing powerful historical analysis using the built in reporting features to give equipment owners detailed insight into the operation and readiness of their equipment fleets.

Proactive service reminders are automatically generated and sent as equipment reaches service intervals based on run-time. Service logs and manuals available over the secure web site reduce paperwork and automate record keeping while providing up to the minute service records for all of your monitored equipment.

Features:

Easy to install cellular monitoring system. A variety of optional enclosures and mounting options provide for a clean and professional installation. Unit includes a quad magnet bracket for quick mounting and templates for mounting with included standoffs.

Advanced power management employing low power idle modes enable the unit to operate in solar powered applications with minimal power draw.

No software to buy, install or maintain; all mapping and data features are accessible over the secure web site from any computer with Internet access.

Technical Specifications:

Size	4.0” x 4.3” x 2.3” in.
Radio	LTE
Digital Inputs	3
Digital Outputs	1
Connectors	5mm Terminal Blocks
GSM Connector	SMA

Power	9 - 32 Volts
Battery Backup	Internal
Current Consumption	
Idle	65 mA
Transmit, Average	250 mA
Peak	2.1 A
Temperature	
Operating	-30°C to +70°C
Storage	-40°C to +85°C
Max. Humidity	95% Non-Condensing

Radio Agency Approvals:

FCC
PTCRB
CE Red
RoHS

Carrier Certification:

AT&T
Verizon

Each Complete Monitoring System Includes:

Digital Cellular Monitoring Unit:
- 3 Digital Inputs
- 1 Digital Output
- Connected 24x7x365
- Monitors Power Voltage
- Battery Backup Included

High Efficiency MLPV LTE (698-2700 MHz) Mag Mount Antenna:
- 3’
- 5‘
- 10’
- 15’

Through hole antenna also available with all cable lengths above.

Mapping & Reporting:
- Web Accessible
- Graphical Map Overview
- Simple User Interface
- Run Service Reports
- Monitor Equipment Use

Alarming & Notifications:
- SMS Text Message
- Email
- Automated Voice Call